



Company Address	Gambit-Lubawka Sp. z o.o., ul. Wojska Polskiego 16, 58-420 Lubawka, Poland
Gasket Type	AF-202
Sealing element dimensions [mm]	92 x 49 x 2

L [mg/(s*m)]	Q _{min/L} [MPa]	Minimum stress to seal Q _{min/L} (at assembly), Q _{Smin/L} (after off-loading) for p = 10 bar									
		Q _{Smin/L} [MPa]									
		Q _A = 10 MPa	Q _A = 20 MPa	Q _A = 40 MPa	Q _A = 60 MPa	Q _A = 80 MPa	Q _A = 100 MPa	Q _A = 120 MPa	Q _A = 140 MPa	Q _A = 160 MPa	
10 ⁰	5	5	5	5	5	5	5			5	
10 ⁻¹	8	5	5	5	5	5	5			5	
10 ⁻²	17		5	5	5	5	5			5	
10 ⁻³	28			5	5	5	5			5	
10 ⁻⁴	39			31	8	5	5			5	
10 ⁻⁵	57				45	14	9			6	
10 ⁻⁶	80					77	33			20	
10 ⁻⁷	132									148	
10 ⁻⁸											



L [mg/(s*m)]	Q _{min/L} [MPa]	Minimum stress to seal Q _{min/L} (at assembly), Q _{Smin/L} (after off-loading) for p = 40 bar									
		Q _{Smin/L} [MPa]									
		Q _A = 10 MPa	Q _A = 20 MPa	Q _A = 40 MPa	Q _A = 60 MPa	Q _A = 80 MPa	Q _A = 100 MPa	Q _A = 120 MPa	Q _A = 140 MPa	Q _A = 160 MPa	
10 ⁰	10	9	5	5	5	5	5			5	
10 ⁻¹	18		10	5	5	5	5			5	
10 ⁻²	30			8	5	5	5			5	
10 ⁻³	44				12	8	6			5	
10 ⁻⁴	64					21	13			9	
10 ⁻⁵	90						55			20	
10 ⁻⁶	128									113	
10 ⁻⁷											
10 ⁻⁸											



Note: the content of darkened cells was not determined respectively is unnecessary Rev - No: 1 Creation date of this sheet: 26.03.2014



